



D-PICO

A skid steer type model with a diesel engine, with exhaust gases and hot air coming out from machine roof, improving the protection and safety of surrounding working areas. This robot arm can be raised to reach higher level areas, increasing the frontal working area. Also includes rapid tool swap, allowing to work with several different tools with little time wast between exchanges.


This machine can work on difficult terrain with maximum productivity and maximum safety. It's design allows it to be easily transportable.

This robot is the most modern tool for forestry, construction or agricultural work, maintenance of green spaces, cleaning of forests, road and highway cleaning, military fields, industrial areas, golf courses, vineyards, etc.



Mower specifications		
Blade rotor	Blades/Teeth	
Maximum rotation	1900 rpm	
Cut width	1 m	

A B



Dimensions	Description	mm
Α	Height	1064
В	Width	1149
С	Machine length	1674
D	Machine length plus Headtool	2166
E	Headtool elevation	1550

2230-836 Fontes ABT	
PORTUGAL	
Tel.: 966292184	
pmachado@ut.com.pt	
1 = 1 3 4 4 1 = 1	

Unmanned Tools - UT. Lda

Sobreira Alta



https://ut.com.pt

General Specifications		
Engine	Kubota 19 kW Stage V	
Fuel type	Diesel	
Fuel tank capacity	20 I	
Hydraulic oil tank	60 I	
Maximum working distance	300 m	
Travel speed (Low/High)	0-4 / 0-8 km/h	
Machine weight + tool	1080 kg	
Maximum working gradient	25º (47%)	
Graphic display interface	Yes	
Quick tool exchange	Yes	
Main tool flow	60 l/min	
Secondary tool flow	25 l/min	
Working pressure	180 bar	